

YUGOROSGAZ - Joint-stock company for gas pipeline network construction and natural gas transportation and trading, Serbia, Belgrade, Zmaj Jovina 8-10

Is announcing

INVITATION FOR SUBMISSION OF BIDS
For supply of steel pipes for gas pipe line Niš - Leskovac

Joint-stock company YUGOROSGAZ, herein after the PURCHASER, is inviting all interesting entities to submit bids for supply of steel pipes:

1. Welded steel preinsulated pipes

Standard: API 5L

Material: X52

Isolated in accordance with: DIN 30670

<u>Dimensions:</u>	<u>kg</u>
Ø 508,0x11,1 mm	81.600
Ø 508,0x8,7 mm	38.880
Ø 508,0x7,9 mm	488.500
Ø 508,0x6,4 mm	1.452.250

2. Welded steel preinsulated pipes

Standard: API 5L

Material: X42

Isolated in accordance with: DIN 30670

<u>Dimensions:</u>	<u>kg</u>
Ø 323,9x9,5 mm	25.778
Ø 323,9x7,1 mm	27.850
Ø 323,9x6,4 mm	323.050
Ø 323,9x5,2 mm	931.500

3. Seamless steel preinsulated pipes

Standard: API 5L

Material: grade B

Isolated in accordance with: DIN 30670

<u>Dimensions:</u>	<u>kg</u>
Ø 168,3x4,8 mm	48.000
Ø 168,3x4,0 mm	6.440

4. Seamless steel pipes

Standard: API 5L

Material: grade B

<u>Dimensions:</u>	<u>kg</u>
Ø 273,1x9,3 mm	9.045

Ø 168,3x7,1 mm	566
Ø 114,3x6,0 mm	322
Ø 88,9x5,5 mm	565
Ø 60,3x3,9 mm	109
Ø 42,2x3,4 mm	68

5. Welded steel pipes for casing

Standard : SRPS EN 10220

Material: S235JRG2

Dimensions:	kg
Ø 610,0x12,5 mm	9.350
Ø 610,0x10,3 mm	45.600
Ø 610,0x7,1 mm	7.420
Ø 457,0x7,1 mm	8.712
Ø 457,0x8,8 mm	16.422
Ø 114,3x3,6 mm	6.839

Quality:	API spec. 5L, PSL 2.
Chemical composition:	API 5L, table 2 B
Mechanical characteristics:	API 5L, par. 6.2
Type of pipe:	EWP with side seam
Seam examining:	according to API 5L par. 9.7.2.2., 9.7.4.1. and 9.7.4.2.
Length of pipe:	12 meters with tolerance according to API 5L table 11.
Ends of pipes:	PE with overturned edges according to API 5L par. 7.9.3.
Certificates :	in accordance with API 5L par. 12.1.2. and SR 15.1. from (a) to (i).
Pipe wall thickness tolerance and pipe weight tolerance:	according to API 5L table 9. и 10.
Max. Hydraulic examining pressure:	according to API 5L par. 9.4.3.
Marking pipe:	according to API 5L par. 10
Isolation:	according to DIN 30670, from LDPE type N, pipe wall thickness (n).
Parity of delivery:	DDU Niš for items 1,3,4 and 5 DDU Leskovac for item 2.

Packaging and marking fees are included.

Term and way of delivery to be necessarily indicated in bid.

The Bidder is required to attach the manufacturer's catalog and reference-list.

A deadline to submit bids in office of Jugorosgaz in Belgrade is 23.03.2010, not later then 3 p.m. The full name and address of the Bidder must be written in sealed envelope with note "Steel pipes".

Decision upon selection of the most favorable Bidder will be made by the Purchaser within 30 days from day of opening the bids.

For all additional information in connection with technical details do not hesitate to contact Mr. Slobodan Ćirić - Project Director, +381 11 321 66 40. Fax. +381 11 321 66 45